

COMMON Baud rates used in serial computer hook ups.

Bauds	Bits/s	Bit duration	Speed	Actual speed	Actual byte duration
50 bauds	50 bits/s	20.000 ms	6.25 bytes/s	5 bytes/s	200.000 ms
75 bauds	75 bits/s	13.333 ms	9.375 bytes/s	7.5 bytes/s	133.333 ms
110 bauds	110 bits/s	9.091 ms	13.75 bytes/s	11 bytes/s	90.909 ms
134 bauds	134 bits/s	7.463 ms	16.75 bytes/s	13.4 bytes/s	74.627 ms
150 bauds	150 bits/s	6.667 ms	18.75 bytes/s	15 bytes/s	66.667 ms
200 bauds	200 bits/s	5.000 ms	25 bytes/s	20 bytes/s	50.000 ms
300 bauds	300 bits/s	3.333 ms	37.5 bytes/s	30 bytes/s	33.333 ms
600 bauds	600 bits/s	1.667 ms	75 bytes/s	60 bytes/s	16.667 ms
1200 bauds	1200 bits/s	833.333 µs	150 bytes/s	120 bytes/s	8.333 ms
1800 bauds	1800 bits/s	555.556 µs	225 bytes/s	180 bytes/s	5.556 ms
2400 bauds	2400 bits/s	416.667 µs	300 bytes/s	240 bytes/s	4.167 ms
4800 bauds	4800 bits/s	208.333 µs	600 bytes/s	480 bytes/s	2.083 ms
9600 bauds	9600 bits/s	104.167 µs	1200 bytes/s	960 bytes/s	1.042 ms
19200 bauds	19200 bits/s	52.083 µs	2400 bytes/s	1920 bytes/s	520.833 µs
28800 bauds	28800 bits/s	34.722 µs	3600 bytes/s	2880 bytes/s	347.222 µs
38400 bauds	38400 bits/s	26.042 µs	4800 bytes/s	3840 bytes/s	260.417 µs
57600 bauds	57600 bits/s	17.361 µs	7200 bytes/s	5760 bytes/s	173.611 µs
76800 bauds	76800 bits/s	13.021 µs	9600 bytes/s	7680 bytes/s	130.208 µs
115200 bauds	115200 bits/s	8.681 µs	14400 bytes/s	11520 bytes/s	86.806 µs
230400 bauds	230400 bits/s	4.340 µs	28800 bytes/s	23040 bytes/s	43.403 µs
460800 bauds	460800 bits/s	2.170 µs	57600 bytes/s	46080 bytes/s	21.701 µs
576000 bauds	576000 bits/s	1.736 µs	72000 bytes/s	57600 bytes/s	17.361 µs
921600 bauds	921600 bits/s	1.085 µs	115200 bytes/s	92160 bytes/s	10.851 µs